

# FM application and rainy weather

The influence of precipitation on trackside FM application in heavy haul environment

Richard Stock, voestalpine Schienen GmbH  
Kevin Oldknow, LB Foster Friction Management




# Overview

- Background
- Test environment
- Methodology
- Results
- Conclusions
- Outlook



# Background (personal)

- voestalpine Schienen GmbH: rail producer from Austria / Europe
- Technical collaboration between voestalpine and Kelsan Technologies since 2004
- Topic: RCF and wear
- Secondment to Kelsan/Vancouver between Mar. 2010 and Nov. 2010



# Background (technical)

- Rain provides noise reduction on transit systems
  - Some transit systems turn FM off while precipitation as no squealing noise is present
- Heavy Haul systems are quite different (loads, train lengths...)
  - What interaction between HH trains and precipitation?



# Test site

- Data used from Western Class 1 Railroad subdivision (L/V site)
- 6 deg (300m) curve
- 1% steady ascending grade
- Superelevation posted for 35 mph (56kph)
- Unit 286k coal trains (loaded) westbound
- Power distribution (head-mid-tail): 2-1-0 and 2-1-1
- Aluminum hoppers, typical train length: 124 cars



# Weather Data

- Weather station at nearby airport (CYVR and 71882)
- Data obtained through <http://www.wunderground.com/>
- Data available per day on an hourly basis (2007 – present)
- Different categories of precipitation – light rain, rain, heavy rain, light snow, snow
- Data on precipitation amount
- Distance between L/V site and weather stations: 3.1 miles (5 km)



# Overview – L/V and Weather stations





# Methodology

- Focus on low rail L/V data – underbalanced train speed (15-20mph – 24-32 kph)
- Identifying days with definite rain conditions between 2007 and present date (rain or heavy rain and more than 0.2inch (0,5cm) daily precipitation)
- Time stamp at L/V site correlated with rain periods
- Only periods between May – September were examined (no snow!)
- Detailed analysis (2008):
  - September 5th – September 22nd: FM application was completely turned off
  - September 22nd – November 30th: FM application was turned on again
  - May – September 2009 and May-September 2010 for confirmation
  - Leading vs. trailing axles





# General analysis – no rain

- All low rail axles used
- 10 axle moving average trend analysis included



# General analysis: rain





- Rain: starting at low L/V values – increase during the first 50 axles
- Similar results for 2009





# Detailed analysis: No FM, dry weather

- September 5th - September 22nd: no FM application
- Dry weather conditions
- L/V low rail: all axles and leading axles only
- Dry results: large data scatter, high L/V values





# Detailed analysis: No FM, rain

- September 5th - September 22nd: no FM application
- Rain conditions
- L/V low rail: all axles and leading axles only
- Rain results:
  - First 50-80 axles increase from low L/V values
  - Separation of leading and trailing axles





# Detailed analysis: FM application, Rain

- After September 22nd : FM application
- Rain conditions
- L/V low rail: all axles and leading axles only
- FM application and rain results:
  - First 50 axles increase from low L/V values to Maximum
  - decrease to nominal values between axles 50-100







# Detailed analysis: FM application, dry weather

- After September 22<sup>nd</sup> 2008: FM application
- Dry weather conditions
- L/V low rail: all axles and leading axles only
- FM application and dry weather results:
  - Some data scatter during the first 50 axles




# Confirmation


## rain and FM application: summer 2009 and 2010




# Wheel Rail Interface – Top of Rail: Bathtub Model



# Third Body Layer – Micron Scale



**Rail**




**Wheel**

Y.Berthier, S. Decartes, M.Busquet et al. (2004). The Role and Effects of the third body in the wheel rail interaction. *Fatigue Fract. Eng. Mater Struct.* 27, 423-436




# “Dry” Wheel / Rail Interface



- Relative Wheel/Rail Motion (Creepage) Accommodated by:  
Rolling(1) – Elasticity(2) – Breaking(3) – Void Collapse(4)




# “FM Treated” Wheel / Rail Interface




**KELTRACK<sup>®</sup> creates a *composite* deformation mechanism**

**Pliable FM particles provide an elastic shear displacement accommodation mechanism that negates/arrests brittle particle breaking and void collapse**



# Film splitting mechanism

- Transfer of liquid FM from rail to wheel and vice-versa
- At and shortly after the FM application bars





# Film splitting




# Explanation – no FM application, dry weather

- No FM, dry weather:
  - Baseline condition, high scatter due to mixture of dry bathtub components (oxides, wear, break shoe debris, environment)




# Explanation – no FM application, rain

- No FM and rain:
  - Wet surface provides initial low friction conditions
  - Rain favors the formation of high friction iron oxides
  - Rain removes some other components on TOR
  - Water will evaporate and high friction oxides will remain resulting in the observed separation of leading and trailing axles



**Initial low L/V**





**Concentrated high L/V**





# Explanation – FM application and dry weather

- FM and dry weather:
  - Film splitting mechanism conditions the wheels of a train




# Explanation – FM application and rain

- FM and rain:
  - Wet surface provides initial low friction conditions
  - Rain favors the formation of high friction iron oxides
  - With every passing wheel the surfaces dry up (first 50 axles) and L/V increases
  - After these first axles the wheels stay dry and conditioned.
  - After these first axles the rail is dry again and FM application is effective again (film splitting mechanism).





# Summary analysis

## first 50 leading axes (Sep. – Nov 2008)



# Verification 2010

- 21 trains between April and Spetmber 2010 for rain and clear conditions
- Analysis for 50 leading axles only and whole train/all leading axles



# Conclusion

- Rain influences directly the first 50-100 axles of a train
- Only the first few axles stay wet – the rest of the train „sees“ no rain
- Absence of FM and rain:
  - Initial L/V increase
  - Concentrated high L/V values due to high friction oxides on TOR
- Presence of FM and rain:
  - Initial L/V increase
  - Decrease to FM controlled L/V for the rest of the train
- Verification of the proposed mechanism necessary.



# Outlook

- Investigation on the influence of snow in next winter
- Laboratory Experiments on the influence of a wet rail surface on the film splitting capability of a wet FM (in progress)
- Abstract submitted to IHHA 2011 (and accepted)



# Thank you for your attention

