

# How Well Does Your Lubricant Track

---

## An Effective Demonstration On San Diego Trolley

**Paolo DiBenedetti**  
**Vice President**  
**Neleco, Inc.**



# Introduction

---

- Wear Reduction Study
- Reasons For Lubricating
  - Noise Issues
  - Wear Issues
  - Reduced Risk Of Low Speed Climb Outs
- Establishing Test
- Observance of tracking



# Introduction

---

- Empirical Evidence
- Material being used
- Rail condition
- Summary
- Implications/Conclusion
- Questions



# **Noise Solutions Rail Wear Reduction The San Diego Trolley Experience**

---

## **Rail Lubrication Strategy**

**Fred Byle, Superintendent Of Wayside  
Maintenance, San Diego Trolley**

**Paolo DiBenedetti, V.P. Neleco, Inc.**



# Problem: Noise

---

- San Diego Trolley had a problem with noise
  - Noise is a significant problem for most transit systems
  - Creates wear on rail
  - Wreaks havoc on ROW and Track staff
  - Constant complaints from public
  - Potentially, leads to threat of lawsuits
- SDTI was a pioneer in reducing noise
  - One of first systems to implement a formal process for addressing noise issues



# Problem Solving

---

- To address the noise issues, San Diego Trolley tried numerous ways of eliminating noise, including:
  - Water
  - Hand applying lubrication
  - Manual Grinding
  - Sound barrier walls
- These all proved unsuccessful, or not cost effective




# Problem Solving

---

- After examining and testing multiple possibilities, SDT then came to gauge face lubrication. After testing and acceptance, Trolley implemented a gauge face lubrication program to address noise issues.
- This gauge face lubrication protocol was implemented in 1998



# Location Of Lubricators



# Measuring Wear

---

- Data Collected Over 14 Years
- Optical Measurements
- Manual Measurements



# Rolling Stock

Model	Acquired	Weight Empty Pounds / Tons	Weight Loaded
Siemens U2	1981	81,500 / 40.75	95,400 / 47.7
Siemens SD 1000	1993	92,000 / 46.0	106,500 / 53.25
Siemens S 70 Long	2004	102,000 / 51.0	118,560 / 59.25
Siemens S 70 Short	2012	98,000 / 49.0	116,840 / 58.4
Low Emission Diesel Locomotive	Rail America	260,000 / 130	2,000 Tons/20 Car Train



# Additional Measuring

---



# Curve # 14 Green (2008)

MTS - SANDIEGO TROLLEY  
MTSGREEN - Track EAST


15/633	Run/Profile	15/634
Nov 28 2008	Run Date	Nov 28 2008
3.813	Mile	3.813
#14: 7.6 deg. R		




# Curve # 14 Green (2011)

MTS - SANDIEGO TROLLEY  
MTSGREEN - Track EAST


56/651	Run/Profile	56/652
Mar 12 2011	Run Date	Mar 12 2011
3.812	Mile	3.812
#14: 7.6 deg. R		



56.37 in.	Gauge	56.37 in.
56.40 in.	Net Gauge	56.40 in.
1.59 mm.	Vertical Wear	1.23 mm.
-0.48 mm.	Gauge Wear	-0.38 mm.
1.59 mm.	Combined Wear	1.23 mm.
4.55 %	Head Loss	3.23 %
0.02 mm.	Gauge Lip	0.00 mm.
0.00 mm.	Field Lip	0.00 mm.
1.2 deg.	Cant	1.6 deg.
0.0 deg.	GFA	0.0 deg.
115RE GREEN	Rail Type Classification	115RE GREEN




# Green Line



# 8<sup>Th</sup> St. Curve (2005)

MTS - SANDIEGO TROLLEY  
MTSBLUE - Track EAST


9/5233	Run/Profile	9/5234
Jul 29 2005	Run Date	Jul 29 2005
4.260	Mile	4.260
#9: 3.0 deg. R		



# 8<sup>Th</sup> St. Curve (2012)


MTS - SANDIEGO TROLLEY  
MTSBLUE - Track EAST

57/4811	Run/Profile	57/4812
Jan 31 2012	Run Date	Jan 31 2012
4.260	Mile	4.260
#9: 3.0 deg. R		



# Blue Line 8<sup>Th</sup> St. Curve

New Rail  
(Zero Wear)




Condemnation  
(Worn Out)



# Establishing A Tracking Test

---



# Establishing A Test

---




# Curves By Line Segment

---

	Blue Line	Green Line	Orange Line
Number Of Curves	13	35	36
Range Of Curves °	1° to 12°	1° to 21°	1° to 14°
Ruling Grade	.9%	4%	3.5%
Miles Per Line	15	12	21



# Location Of Lubricators



# Lubricator Installation

---



# Applicator Bar

---



# Applicator Bar

---



# Lubricator Settings Volume Applied

---

Axle Count Setting Run Time	Train Passes Day	Volume Lubricant Applied Per Pass	Total Axle Count	Total Volume Applied
16 Axles 4 Seconds	72	0.4 cu. inch	1,152	28.8 cu. in
34 Days	2448		39,168	979.2 cu. in.



# Horse-Shoe Curve

---




# Fluorescent Lubricant

---




# Testing

---



# Testing

---



# Initial Finding


---

- Lubricator was installed March 6
- First observance March 8
- Next Check March 11
- Tracked 1.05 miles in 5 days



# Dyed Lubricant In Reservoir

---



# Photographic Evidence

---

- April 8 and April 9
- Strong Evidence Of Lubricant
- Fluorescent Dye Overwhelmed
- Swipe Test



# Photographic Evidence

---



# Swipe Test

---



# Swipe Test

---



# Evidence Of Lubricant

---



# Evidence Of Lubricant

---



# Evidence Of Lubricant

---




# End Of Test Track

---




# Additional Observation Area's



# At 12<sup>Th</sup> And Imperial

---



# Old Town TC

---



# Rail Condition

---

- Maintenance
- Grinding
- Profiling
- Lubricant
- Lubricators



# Tracking Distance Summary

---

## Location

## Miles Of Tracking

- |   |                      |
|---|----------------------|
| • Test Site Orange Line                   | • 9.55 Miles         |
| • Blue Line 12 <sup>Th</sup> And Imperial | • 13.75 Miles        |
| • Green Line Old Town Transit Center      | • 11.0 Miles or more |



# Summary

---

- Reduction Of Wear
- Noise Abatement
- Effective Collection Of Evidence
- Effectiveness Elsewhere on Trolley
- Conditions For Maximum Effectiveness



# Implications/Conclusions

---

- Extended Life Of Rail
- Noise Abatement
- Rail Maintenance
- ROI
- Protection Of Asset



# Questions

---

